

Panel 640-zone IP + 2G home security system via radio (Z-Wave, Zigbee and WiFi optional)



Specifications

- 640 radio zones
- 640 users
- 8 partitions
- TCP/IP and 2G communication (optional WiFi pin)
- Incorporates 2G module
- Supports RF 868-SF1 devices
- Supports HD transmission devices (PIRCAMS) and SF1 bidirectional audio
- Amplified fast connection for external GPRS antenna (not included, **VESTA-274** recommended)
- Reporting methods: CID/SIA, Email, SMS, Push Notification
- Programming methods: Web and App
- Live visual verification
- Home automation

- Energy management
- 24/7 emergency monitoring
- Remote management
- Built-in siren
- RF Frequency: 868MHz
- 2G Frequency: 850/900/1800/1900MHz
- Power supply: 12V, 1A
- Backup battery: 7.2V, 1100mAh, Ni-mH, rechargeable
- Battery life of 13 hours
- Ready to support high capacity external battery (**DEM-8M-BACKUP** and **DEM-9M-BACKUP**)
- Includes Mini USB quick connector for external organic battery connection
- Operating temperature -10°C ~ +45°C (-10°C ~ +45°C)
- Relative humidity: Up to 85% (non-condensing)
- Dimensions: 140 (W) x 150 (H) x 42 mm
- Certified EN50131 Grade 2, Environmental Class II
- VESTA's Gateway via radio is compatible with Google Home and Alexa
- Integration with Aeotec or Fibaro Z-Wave automatic devices (Fibaro Dimmer 2, Roller Shutter 3, Smart Module, Single Switch 2) via not included dongle module **VESTA-240** (ZW-DONGLE)
- Includes Mini USB quick connector for external organic battery connection